Used equipment

For sale by Intercem

1 pre-owned 12 spouts packing machine

I01003

On offer: a pre-owned 12 spouts roto packing machine including bag discharge conveyors from Haver & Boecker, a high quality German supplier. The packing plant could be completed with new and used items on demand. Additional customized solutions (e.g. refurbishing, detail engineering) are available on demand.

<u>Technical specification:</u>

supplier: Haver & Boecker, Germany

type: 12 RS MEC 2 - N

build in: 1994

capacity: 4000 bags / h, bag size 25 kg

3000 bags / h, bag size 50 kg

bag placer: Radimat (Bags on roll)

■ motor: 500 V; 50 Hz

If interested, please contact:

Mr. Wadim Wir, Phone: +49 2522 92058-0, used@intercem.de

Intercem Engineering GmbH Carl-Zeiss-Str. 10 59302 Oelde, Germany

Phone: +49 2522 92058-0 Fax: +49 2522 92058-20

Web: intercem.de

Intercem Engineering is a leading company for the supply of pre-owned and new equipment and services for the cement industry. Turn key plants are designed as combination of used and (where necessary) new equipment. A top notch team of engineers also provides comprehensive engineering of the technology and design of complete new production lines. The component decribed above could be implemented in a comprehensive solution upon demand.





Roto packer 12

Bag cleaning

Weigh bridge

Bag discharge







1 Rotation drive: Gear motor with frequency converter

motor output: 2.20 kW

- 1 Residual emptying device
- 1 Spillage rejecting flap
- 1 Server MEC II 20 + N

The used existing SERVER has to be sent to HAVER & BOECKER by customer in time of order to allow the installation of the SERVER into new operator panel.

• 1 Bag discharge belt conveyor

center distance: 1300 mm drive: 1.50 kW required dedusting air quantity: 1500 m³/h





Bag discharge belt conveyor

- 1 Manual height adjusting device
- 1 Bag pile-up control
- 1 Bag directing belt conveyor

drive: 1.10 kW

1 Bag cleaning station

dedusting air quantity: 4000 m³/h



Bag cleaning station

Fast Fair Flexible

• 1 Acceleration conveyor

drive: 1.10 kW

• 1 Interface for remote adjustment

Bag rejecting device (telescopic-design) for removal of broken bags and
bags below the target.

bags below the target.

belt drive: 1.10 kW telescopic drive: 1.50 kW dedusting air quantity: 500 m³/h

• 1 Check weigher

belt drive: 0.75 kW



Check weigher

Not included in the scope of supply!

- **1.** Screws under the bag discharge line and dust collector bin.
- 2. Roll holder for "Radimat" bag placer.
- 3. Dust collector bin under the packing machine.
- 4. All Cabinets.
- **5**. Bag cleaning fan for bag cleaner.
- **6**. Rewinding of motors to 400 V if required.



5/5 I01003 12/2016